



Project: _____

Location: _____

Cat. #: _____

Type: _____

Quantity: _____

LED

XWL LED Wet Location Exit

Features:

- Ultra-bright, long life Red or Green LED
- Dual 120/277V
- Unique bi-color LED indicator light alerts occupant on battery condition
 - Green - Normal
 - Red - Check Battery
- 4.8V long life, maintenance free, rechargeable NiCd battery
- Internal solid-state transfer switch automatically connects the internal battery to LED board for minimum 90-minute emergency illumination
- Fully automated solid-state, two rate charger initiates battery charging to recharge a discharged battery in 24 hours
- Easy snap-out chevron directional indicators
- Custom signs available with custom wording



Applications:

For use in damp or wet locations where exit signage is needed.

Ambient Operating Temp:

-20°C - 50°C

Construction:

- 5VA flame retardant, UV-stabilized polycarbonate housing
- Impact resistant, UV-stabilized polycarbonate clear lens
- Corrosion-resistant enclosure with engineering grade silicone gasket
- Top and side K/O's for conduit feed

Mounting:


- Polycarbonate mounting canopy included for top or end mount
- Universal K/O pattern on back plate for wall mount

Certifications:

- UL listed for wet locations
- UL924
- NFPA 101 Life Safety Code
- NEC
- OSHA
- Local and State Codes

Warranty:

- 5 year limited warranty on housing and electronics. Battery pro rated for 5 yrs.
- see www.UnamiLighting.com for complete warranty terms and conditions



Ordering Guide:

example: XWL 2 R DV W CW-EM SD

Series	# of Faces	Letter Color	Voltage	Housing Color	Ambient Temp	-	Battery	Options
WLE			DV		CW	-		
WLE LED Wet Location Exit	1 Single Face 2 Double Face	R Red G Green	DV Dual 120/277V	W White w/ White Faceplate B Black w/ Black Faceplate G Gray w/ White Faceplate	CW Cold Weather		Blank AC Only EM Battery Backup	Blank None SD Self Diagnostics (EM units only) TP Tamper Proof 2C Dual Circuit (AC units only) Custom() Custom wording (specify wording)

Electrical Chart:

Catalog #	Input Watts (W)	Input Watts (W)	Input Amps (A)	Input Amps (A)
	120V	277V	120V	277V
XWL-RED/GREEN	2.7	2.7	0.025	0.011
XWL-RED/GREEN/EM/SD	3.3	3.4	0.030	0.014
XWL-RED/GREEN/2C	2.4	2.4	0.023	0.011

Schematic:

